

# Tomato Caustic Peelers

Model CA-30 and CA-50



Consistently excellent quality with maximized yields

## General Description

JBT Tomato Caustic Peelers provide precise, efficient peeling of all tomato varieties at 25-60 tons per hour. A bucket conveyor system carries the tomatoes through the caustic solution. The tomatoes are then transported to the peel remover. Variable bucket conveyor speed accommodates individual product requirements. Two circulation pumps maintain even caustic temperature throughout the tank.

Filters remove foreign matter from the solution. Fingertip control for immersion time, temperature, caustic concentration and density is standard.

### Product Feature

### Processor Benefit

Automatic temperature and density controls

Consistently excellent quality with maximized yields

Complete immersion of product in the caustic bath

High peeling efficiency

Optional By-Product Recovery System


Minimizes operating costs, maximizes by-product value

Inverted bucket principle transports product while keeping it totally immersed

Gentle product handling retains high product quality

Optional Steam Preheater for Caustic Peelers

Increases capacity up to 20% or reduces caustic usage



DIMENSIONS	CA-30 WITH RCS AND 12' PINCH BED	CA-50 WITH RCS-HV AND 16' PINCH BED
A	42 ft. (12802 mm)	53 ft. (16154 mm)
B	9 ft. 8 in. Varies per installation (2946 mm)	10 ft. 3 in. Varies per installation (3124 mm)
C	15 ft. Varies per installation (4572 mm)	16 ft. 6 in. Varies per installation (5029 mm)

TECHNICAL SPECIFICATIONS	CA-30	CA-50
Feed Height	5 ft. 5-1/4 in. (1657mm)	6 ft. (1829 mm) Varies per installation
Discharge Height	7 ft. 6 in. (2286 mm)	7 ft. 6 in. (2286 mm) Varies per installation
Width Overall	7 ft. 3-1/4 in. (2216 mm)	7 ft. 3-1/4 in. (2216 mm) Varies per installation
Water	1 in. inlet (25.4 mm)	1 in. inlet (25.4 mm)
Electricity	29.2 kW	31.0 kw
Air	1 cfm at 50 psi (472 cu. cm at 35160 kg/m <sup>2</sup> )	2 cfm at 50 psi (944 cu. cm @ 35160 kg/m <sup>2</sup> )
Steam	1800 lbs/h (818 kg/h)	2700 lbs/hr (1227 kg/hr)
Caustic Usage	2.2 gal (8.3 liters) 50% NaOH liquid per ton of input product	2.2 gal (8.3 liter) 50% NaOH liquid per ton of input product
Dipper Solution Capacity	925 gal (3500 liters)	1400 gal (5300 liters)
General Operating Range	25-40 t/h (22-36 MT/h)	45-60 t/hr (41-54 MT/hr)

(All specifications are approximate)

### COUNT ON JBT TO HELP PROTECT YOUR INVESTMENT

JBT's greatest value in PRoCARE® services comes from preventing unexpected costs through smart, purposeful, and timely maintenance based on unmatched knowledge and expertise. PRoCARE service packages are offered as a maintenance agreement in various service levels, depending on your production and cost management requirements.



### JBT LIQUID FOODS

FRESH PRODUCE TECHNOLOGIES | FRESH-CUT, ROBOTICS, STEAMING | FRUIT AND VEGETABLE PROCESSING | SECONDARY PROCESSING | ASEPTIC SYSTEMS | FILLING AND CLOSING | IN-CONTAINER STERILIZING | TRAY SEALING | HIGH-PRESSURE PROCESSING | POWDER PROCESSING | TUNA PROCESSING

### OUR BRANDS



### North America

John Bean Technologies Corporation  
2300 Industrial Avenue  
Madera CA 93639  
USA  
Phone: +1 559 661 3200  
Fax: +1 559 661 3156

### Europe

John Bean Technologies SpA  
Via Mantova 63/A  
43122 Parma  
Italy  
Phone: +39 0521 908 411  
Fax: +39 0521 460 897

### South America

John Bean Technologies  
Máq. e Equip. Ind. Ltda.  
Av. Eng Camilo Dinucci 4605  
14808-900 Araraquara, São Paulo  
Brazil  
Phone: +55 16 3301 2000  
Fax: +55 16 3301 2144

### Asia Pacific

John Bean Technologies (Shanghai) Co., Ltd.  
Room 1908, Hongwell International Plaza,  
1600 West Zhongshan Road,  
Xuhui District, Shanghai 200235,  
PRC  
Phone: +86 21 3339 1588  
Fax: +86 21 3339 1599



We're with you, right down the line.™

madera.fpsd@jbt.com | hello@jbt.com | [jbt.com](http://jbt.com)

