



JBT Certified Lubricants

# Food-grade Formula 352

Antiwear extreme high-temperature H1 food-grade grease



You chose Double D equipment from JBT for your process line because of their proven performance – in extended production, under heavy loads, and at extreme temperatures.

## Your single source

Choose our food-grade Formula equipment greases for the same reasons. Protect your food processing investment at the same time you simplify your supply of a complete range of equipment customized and safety-certified greases.

## What's unique with Formula 352 grease?

- Grease developed and tested to fit JBT's Double D Revoband oven fan shaft.
- Perfect "cocktail" of pourpoint and viscosity.
- JBT can offer a PRoCARE service agreement package which provides all the necessary greases.

# Food-grade Formula 352

## Description

Formula 352 is a grease based on synthetic polyalphaolefin (PAO) specially developed for JBT's Double D Revoband oven fan shaft. The grease answers the stringent food safety- and hygiene requirements and temperature extremes of the food processing industry. Tested and proven in extremely high temperatures with maintained performance stability and to protect components against corrosion, rust and oxidation. The Formula 352 grease support safe, smooth operation and maximized operating uptime. Choose the JBT Food-grade Formula 352 grease to extend the running hours of your equipment.

## Formula 352 Features

- High Temperature Performance
- Anti-Wear Protection
- Non-Melting Performance
- Rust Inhibiting
- Oxidation Protection
- Effective Lubricity throughout the Full Operational Temperature Spectrum
- Meets Food-grade H1 Requirements for Incidental Food Contact

## Benefits for your application

- Improved lifetime of parts.
- Lower maintenance costs.
- Improved uptime.

Don't jeopardize your production by using non-recommended greases because, in the end, they can cost you more! Experience shows that they can lead to expensive equipment failure and lost production time.

The European Union now applies ISO standards

that require food processors to use greases that are completely harmless to the food product's consumer, if cross-contamination occurs. JBT can give you that certification today.

Please contact your JBT representative for detailed specifications and price information for each product, and to learn about greases for our other applications.

As always, we stand behind what we sell. One call gets it all.

## Technical Data

Penetration, Worked	265-295
NLGI Grade	2
Pour point	- 53°C
Dropping point	343°C
Texture	Smooth/Tacky
Colour	Clear
Base Fluid:	PAO Synthetic
Viscosity at 40°C, cSt	60-65
Viscosity at 100°C, cSt	9.4-10.2
Viscosity Index	135
Containers	10 Cartridge Pack - 397 grams / pcs



### Sweden

John Bean Technologies AB  
Rusthällsgatan 21, Box 913  
SE-251 09 Helsingborg  
SWEDEN  
Phone: +46 42 490 4000  
Fax: +46 42 490 4040

### Spain

John Bean Technologies S.L  
A2, Kilómetro 34,400  
28805 Alcalá de Henares, Madrid  
SPAIN  
Phone: +34 913 046 698  
Fax: +34 913 272 266

### UK

John Bean Technologies Ltd  
East Mains Industrial Estate,  
Broxburn, West Lothian EH52 5NP,  
Scotland, UK  
Phone: +44 1506 857112  
Fax: +44 1506 852232

### Poland

John Bean Technologies Sp. z o.o  
Al. Komisji Edukacji Narodowej  
53 m.4  
PL-02 797 Warszawa, POLAND  
Phone: +48 22 894 9025  
Fax: +48 22 894 9041

### Russia

John Bean Technologies LLC  
ul. Petrovka 27, Entrance 2  
RU-10731 Moscow  
RUSSIA  
Phone: +7 495 221 8713  
Fax: +7 495 221 8714

### Germany

John Bean Technologies GmbH  
Siemensstrasse 6  
40885 Ratingen  
GERMANY  
Phone: +49 2102 9341 0  
Fax: +49 2102 9341 31

### France

John Bean Technologies SA  
Taverparc – Bâtiment 2.1  
62 Boulevard Henri Navier  
95150 Taverny, FRANCE  
Phone: +33 (0) 184 28 0200

### Italy

John Bean Technologies SpA  
Via Mantova 63/A  
43122 Parma  
ITALY  
Phone: +39 052 1908411  
Fax: +39 052 1908579

www.jbtfoodtech.com