



## SHACKLE WASHER MODELS: SW-2 to SW-8





## **Technical Specifications**

Electrical Requirements: (2) 3/4 hp motors 208-230/460 V 3ph, 60hz

Water Requirements: Connections: (2) 3/4" NPT female Pressure: Plant pressure (30-60 psi) Nozzles: 5010 1/4" NPD Fan Spray Nozzle

The SW-4 and SW-6 Shackle Washers provide an efficient and effective solution for in-line washing of shackles. Mounted to any spot on the overhead line, the washer cleans shackles, trolleys and chain simultaneously. Each brush is driven by a separate motor and can be adusted individually. Cleaning water is supplied separately to each brush, increasing cleaning efficiency. Three different brushes are available: nylon, black twisted (above) and silica carbide-impregnated bristles that will also polish stainless shackles in addition to cleaning.

FOR ON-LINE SHACKLE LINE CLEANING

INCLUDES MANUAL HYDRAULIC ADJUSTER

STAINLESS STEEL CASE PREVENTS SPLASHING

THREE DIFFERENT BRUSHES AVAILABLE



At Prime Equipment Group, we work closely with our customers and help to design and customize our equipment systems in order to provide you with the most effcient, safe, and profittable solution for your production requirements.

From customized cone deboning lines, product transfer conveyors, to custom conveyors with trim stations, we have the knowledge and experience to provide you with the best possible solution for your next plant project.







